



# New Jersey Department of Health and Senior Services

## HAZARDOUS SUBSTANCE FACT SHEET

Common Name: **AMMONIUM CHROMATE**

CAS Number: 7788-98-9

DOT Number: NA 9086

RTK Substance number: 0095

Date: October 1986 Revision: February 1998

### HAZARD SUMMARY

- \* **Ammonium Chromate** can affect you when breathed in and by passing through your skin.
- \* Eye contact can cause severe irritation with possible loss of vision.
- \* Skin contact can cause severe irritation and burns and may cause deep ulcers.
- \* Exposure can irritate the nose, throat and lungs with cough and/or wheezing.
- \* Breathing **Ammonium Chromate** can cause a sore or hole in the "bone" (septum) dividing the inner nose, sometimes with bleeding, discharge and/or formation of a crust.
- \* **Ammonium Chromate** may cause a skin allergy. If allergy develops, very low future exposures can cause itching and a skin rash.
- \* Repeated or severe exposure may cause kidney damage.

### IDENTIFICATION

**Ammonium Chromate** is a yellow crystalline (sugar or sand-like) material which can be used in solution. It is used to inhibit corrosion, in dyeing textiles, photography, and in chemical reactions.

### REASON FOR CITATION

- \* **Ammonium Chromate** is on the Hazardous Substance List because it is regulated by OSHA and cited by ACGIH, NIOSH, DOT, DEP and EPA.
- \* Definitions are provided on page 5.

### HOW TO DETERMINE IF YOU ARE BEING EXPOSED

The New Jersey Right to Know Act requires most employers to label chemicals in the workplace and requires public employers to provide their employees with information and training concerning chemical hazards and controls. The federal OSHA Hazard Communication Standard, 1910.1200, requires private employers to provide similar training and information to their employees.

- \* Exposure to hazardous substances should be routinely evaluated. This may include collecting personal and area air samples. You can obtain copies of sampling results from your employer. You have a legal right to this information under OSHA 1910.20.
- \* If you think you are experiencing any work-related health problems, see a doctor trained to recognize occupational diseases. Take this Fact Sheet with you.

### WORKPLACE EXPOSURE LIMITS

The following exposure limits are for *Chromium compounds* (measured as *Chromium*):

OSHA: The legal airborne permissible exposure limit (PEL) is **0.1 mg/m<sup>3</sup>** not to be exceeded at any time.

NIOSH: The recommended airborne exposure limit is **0.001 mg/m<sup>3</sup>** averaged over a 10-hour workshift.

ACGIH: The recommended airborne exposure limit is **0.05 mg/m<sup>3</sup>** averaged over an 8-hour workshift.

- \* The above exposure limits are for air levels only. When skin contact also occurs, you may be overexposed, even though air levels are less than the limits listed above.

### WAYS OF REDUCING EXPOSURE

- \* Enclose operations and use local exhaust ventilation at the site of chemical release. If local exhaust ventilation or enclosure is not used, respirators should be worn.
- \* Wear protective work clothing.
- \* Wash thoroughly immediately after exposure to **Ammonium Chromate** and at the end of the workshift.
- \* Post hazard and warning information in the work area. In addition, as part of an ongoing education and training effort, communicate all information on the health and safety hazards of **Ammonium Chromate** to potentially exposed workers.

This Fact Sheet is a summary source of information of all potential and most severe health hazards that may result from exposure. Duration of exposure, concentration of the substance and other factors will affect your susceptibility to any of the potential effects described below.

-----

## HEALTH HAZARD INFORMATION

### Acute Health Effects

The following acute (short-term) health effects may occur immediately or shortly after exposure to **Ammonium Chromate** :

- \* Eye contact can cause severe irritation with possible loss of vision.
- \* Skin contact can cause severe irritation and burns and may cause deep ulcers.
- \* Exposure can irritate the nose, throat and lungs with cough and/or wheezing.

### Chronic Health Effects

The following chronic (long-term) health effects can occur at some time after exposure to **Ammonium Chromate** and can last for months or years:

### Cancer Hazard

- \* While **Ammonium Chromate** has not been identified as a carcinogen, certain kinds of *Chromium compounds*, known as hexavalent *Chromium* or *Chromium VI compounds*, have been determined to be human carcinogens. **Ammonium Chromate** is such a compound and should therefore be handled with extreme caution.

### Reproductive Hazard

- \* According to the information presently available to the New Jersey Department of Health and Senior Services, **Ammonium Chromate** has not been tested for its ability to affect reproduction.

### Other Long-Term Effects

- \* Breathing **Ammonium Chromate** can cause a sore or hole in the "bone" (septum) dividing the inner nose, sometimes with bleeding, discharge and/or formation of a crust.
- \* **Ammonium Chromate** may cause a skin allergy. If allergy develops, very low future exposures can cause itching and a skin rash.
- \* Repeated or severe exposure may cause kidney damage.

## MEDICAL

### Medical Testing

For those with frequent or potentially high exposure (half the TLV or greater), the following are recommended before beginning work and at regular times after that:

- \* Exam of the skin and nose.

If symptoms develop or overexposure is suspected, the following may be useful:

- \* Kidney function tests.
- \* Evaluation by a qualified allergist, including careful exposure history and special testing, may help diagnose skin allergy.

Any evaluation should include a careful history of past and present symptoms with an exam. Medical tests that look for damage already done are not a substitute for controlling exposure.

Request copies of your medical testing. You have a legal right to this information under OSHA 1910.20.

### Mixed Exposures

Because smoking can cause heart disease, as well as lung cancer, emphysema, and other respiratory problems, it may worsen respiratory conditions caused by chemical exposure. Even if you have smoked for a long time, stopping now will reduce your risk of developing health problems.

### Conditions Made Worse By Exposure

- \* Persons with any cuts or scratches on their hands or other skin surfaces are at increased risk of developing ulcers on skin contact. Work practices, protective clothing or removal from exposure is essential to prevent serious ulcers.
- \* Persons with a history of skin allergy to *Chromium compounds* can have a severe rash with skin exposure to **Ammonium Chromate**.

## WORKPLACE CONTROLS AND PRACTICES

Unless a less toxic chemical can be substituted for a hazardous substance, **ENGINEERING CONTROLS** are the most effective way of reducing exposure. The best protection is to enclose operations and/or provide local exhaust ventilation at the site of chemical release. Isolating operations can also reduce exposure. Using respirators or protective equipment is less effective than the controls mentioned above, but is sometimes necessary.

In evaluating the controls present in your workplace, consider: (1) how hazardous the substance is, (2) how much of the substance is released into the workplace and (3) whether harmful skin or eye contact could occur. Special controls should be in place for highly toxic chemicals or when significant skin, eye, or breathing exposures are possible.

In addition, the following control is recommended:

- \* Where possible, automatically pump or transfer **Ammonium Chromate** from drums or other storage containers to process containers.

Good **WORK PRACTICES** can help to reduce hazardous exposures. The following work practices are recommended:

- \* Workers whose clothing has been contaminated by **Ammonium Chromate** should change into clean clothing promptly.
- \* Do not take contaminated work clothes home. Family members could be exposed.
- \* Contaminated work clothes should be laundered by individuals who have been informed of the hazards of exposure to **Ammonium Chromate**.
- \* Eye wash fountains should be provided in the immediate work area for emergency use.
- \* If there is the possibility of skin exposure, emergency shower facilities should be provided.
- \* On skin contact with **Ammonium Chromate**, immediately wash or shower to remove the chemical.
- \* Do not eat, smoke, or drink where **Ammonium Chromate** is handled, processed, or stored, since the chemical can be swallowed. Wash hands carefully before eating or smoking.
- \* Use a vacuum or a wet method to reduce dust during clean-up. **DO NOT DRY SWEEP**.
- \* When vacuuming, a high efficiency particulate absolute (HEPA) filter should be used, not a standard shop vacuum.

## PERSONAL PROTECTIVE EQUIPMENT

WORKPLACE CONTROLS ARE BETTER THAN PERSONAL PROTECTIVE EQUIPMENT. However, for some jobs (such as outside work, confined space entry, jobs done only once in a while, or jobs done while workplace controls are being installed), personal protective equipment may be appropriate.

OSHA 1910.132 requires employers to determine the appropriate personal protective equipment for each hazard and to train employees on how and when to use protective equipment.

The following recommendations are only guidelines and may not apply to every situation.

### Clothing

- \* Avoid skin contact with **Ammonium Chromate**. Wear protective gloves and clothing. Safety equipment suppliers/manufacturers can provide recommendations on the most protective glove/clothing material for your operation.
- \* All protective clothing (suits, gloves, footwear, headgear) should be clean, available each day, and put on before work.

### Eye Protection

- \* Wear splash-proof chemical goggles and face shield when working with liquid, unless full facepiece respiratory protection is worn.
- \* Wear dust-proof goggles and face shield when working with powders or dust, unless full facepiece respiratory protection is worn.

### Respiratory Protection

#### IMPROPER USE OF RESPIRATORS IS DANGEROUS.

Such equipment should only be used if the employer has a written program that takes into account workplace conditions, requirements for worker training, respirator fit testing and medical exams, as described in OSHA 1910.134.

- \* Where the potential exists for exposures over **0.001 mg/m<sup>3</sup>**, use a MSHA/NIOSH approved supplied-air respirator with a full facepiece operated in a pressure-demand or other positive-pressure mode. For increased protection use in combination with an auxiliary self-contained breathing apparatus operated in a pressure-demand or other positive-pressure mode.
- \* Exposure to **15 mg/m<sup>3</sup>** is immediately dangerous to life and health. If the possibility of exposure above **15 mg/m<sup>3</sup>** exists, use a MSHA/NIOSH approved self-contained breathing apparatus with a full facepiece operated in a pressure-demand or other positive-pressure mode.

## QUESTIONS AND ANSWERS

- Q: If I have acute health effects, will I later get chronic health effects?
- A: Not always. Most chronic (long-term) effects result from repeated exposures to a chemical.
- Q: Can I get long-term effects without ever having short-term effects?
- A: Yes, because long-term effects can occur from repeated exposures to a chemical at levels not high enough to make you immediately sick.

Q: What are my chances of getting sick when I have been exposed to chemicals?

A: The likelihood of becoming sick from chemicals is increased as the amount of exposure increases. This is determined by the length of time and the amount of material to which someone is exposed.

Q: When are higher exposures more likely?

A: Conditions which increase risk of exposure include dust releasing operations (grinding, mixing, blasting, dumping, etc.), other physical and mechanical processes (heating, pouring, spraying, spills and evaporation from large surface areas such as open containers), and "confined space" exposures (working inside vats, reactors, boilers, small rooms, etc.).

Q: Is the risk of getting sick higher for workers than for community residents?

A: Yes. Exposures in the community, except possibly in cases of fires or spills, are usually much lower than those found in the workplace. However, people in the community may be exposed to contaminated water as well as to chemicals in the air over long periods. Because of this, and because of exposure of children or people who are already ill, community exposures may cause health problems.

-----  
The following information is available from:

New Jersey Department of Health and  
Senior Services  
Occupational Disease and Injury Services  
Trenton, NJ 08625-0360  
(609) 984-1863

#### **Industrial Hygiene Information**

Industrial hygienists are available to answer your questions regarding the control of chemical exposures using exhaust ventilation, special work practices, good housekeeping, good hygiene practices, and personal protective equipment including respirators. In addition, they can help to interpret the results of industrial hygiene survey data.

#### **Medical Evaluation**

If you think you are becoming sick because of exposure to chemicals at your workplace, you may call a Department of Health and Senior Services physician who can help you find the services you need.

#### **Public Presentations**

Presentations and educational programs on occupational health or the Right to Know Act can be organized for labor unions, trade associations and other groups.

#### **Right to Know Information Resources**

The Right to Know Infoline (609) 984-2202 can answer questions about the identity and potential health effects of chemicals, list of educational materials in occupational health, references used to prepare the Fact Sheets, preparation of the Right to Know survey, education and training programs, labeling requirements, and general information regarding the Right to Know Act. Violations of the law should be reported to (609) 984-2202.

-----

## DEFINITIONS

**ACGIH** is the American Conference of Governmental Industrial Hygienists. It recommends upper limits (called TLVs) for exposure to workplace chemicals.

A **carcinogen** is a substance that causes cancer.

The **CAS number** is assigned by the Chemical Abstracts Service to identify a specific chemical.

A **combustible** substance is a solid, liquid or gas that will burn.

A **corrosive** substance is a gas, liquid or solid that causes irreversible damage to human tissue or containers.

**DEP** is the New Jersey Department of Environmental Protection.

**DOT** is the Department of Transportation, the federal agency that regulates the transportation of chemicals.

**EPA** is the Environmental Protection Agency, the federal agency responsible for regulating environmental hazards.

A **fetus** is an unborn human or animal.

A **flammable** substance is a solid, liquid, vapor or gas that will ignite easily and burn rapidly.

The **flash point** is the temperature at which a liquid or solid gives off vapor that can form a flammable mixture with air.

**HHAG** is the Human Health Assessment Group of the federal EPA.

**IARC** is the International Agency for Research on Cancer, a scientific group that classifies chemicals according to their cancer-causing potential.

A **miscible** substance is a liquid or gas that will evenly dissolve in another.

**mg/m<sup>3</sup>** means milligrams of a chemical in a cubic meter of air. It is a measure of concentration (weight/volume).

**MSHA** is the Mine Safety and Health Administration, the federal agency that regulates mining. It also evaluates and approves respirators.

A **mutagen** is a substance that causes mutations. A **mutation** is a change in the genetic material in a body cell. Mutations can lead to birth defects, miscarriages, or cancer.

**NAERG** is the North American Emergency Response Guidebook. It was jointly developed by Transport Canada, the United States Department of Transportation and the Secretariat of Communications and Transportation of Mexico. It is a guide for first responders to quickly identify the specific or generic hazards of material involved in a transportation incident, and to protect themselves and the general public during the initial response phase of the incident.

**NCI** is the National Cancer Institute, a federal agency that determines the cancer-causing potential of chemicals.

**NFPA** is the National Fire Protection Association. It classifies substances according to their fire and explosion hazard.

**NIOSH** is the National Institute for Occupational Safety and Health. It tests equipment, evaluates and approves respirators, conducts studies of workplace hazards, and proposes standards to OSHA.

**NTP** is the National Toxicology Program which tests chemicals and reviews evidence for cancer.

**OSHA** is the Occupational Safety and Health Administration, which adopts and enforces health and safety standards.

**PEOSHA** is the Public Employees Occupational Safety and Health Act, a state law which sets PELs for New Jersey public employees.

**ppm** means parts of a substance per million parts of air. It is a measure of concentration by volume in air.

A **reactive** substance is a solid, liquid or gas that releases energy under certain conditions.

A **teratogen** is a substance that causes birth defects by damaging the fetus.

**TLV** is the Threshold Limit Value, the workplace exposure limit recommended by ACGIH.

The **vapor pressure** is a measure of how readily a liquid or a solid mixes with air at its surface. A higher vapor pressure indicates a higher concentration of the substance in air and therefore increases the likelihood of breathing it in.

Hazard rating	NJDHSS	NFPA
<b>FLAMMABILITY</b>	Not Found	Not Rated
<b>REACTIVITY</b>	Not Found	Not Rated
CONTAINERS MAY EXPLODE WHEN HEATED POISONOUS GASES ARE PRODUCED IN FIRE		

## FIRE HAZARDS

- ## SPILLS AND EMERGENCIES

CHEMTREC: (800) 424-9300  
NJDEP HOTLINE: (609) 292-7172

- \* Prior to working with **Ammonium Chromate** you should be trained on its proper handling and storage.
- \* **Ammonium Chromate** must be stored to avoid contact with COMBUSTIBLE, ORGANIC or OTHER EASILY OXIDIZED MATERIALS (such as PAPER, WOOD, SULFUR, ALUMINUM, HYDRAZINE and PLASTICS) since violent reactions occur.
- \* Store in tightly closed containers in a cool, well-ventilated area away from HEAT and ANY CONDITION WHICH COULD SHOCK IT.
- \* Sources of ignition, such as smoking and open flames, are prohibited where **Ammonium Chromate** is used, handled, or stored in a manner that could create a potential fire or explosion hazard.

*In NJ, POISON INFORMATION 1-800-764-7661*

\* Immediately flush with large amounts of water. Continue without stopping for at least 30 minutes, occasionally lifting upper and lower lids. Seek medical attention immediately.

\* Quickly remove contaminated clothing. Immediately wash contaminated skin with large amounts of water.

- \* Remove the person from exposure.
- \* Begin rescue breathing if breathing has stopped and CPR if heart action has stopped.
- \* Transfer promptly to a medical facility.

**Water Solubility:** Soluble

### Chromic Acid, Diammonium Salt

### Diammonium Chromate; Neutral Ammonium Chromate

*Not intended to be copied and sold for commercial purposes.*

## Right to Know Program

PO Box 368, Trenton, NJ 08625-0368  
(609) 984-2202